- 1-32. (canceled)
- **33**. A method comprising:
- receiving, by an apparatus, wireless communication service from a first access point;
- detecting, by the apparatus, a change in fingerprint data relating to available access points;
- correlating, by the apparatus, recent history data of a series of fingerprint data with history data comprised by a history database;
- determining, by the apparatus, in response to the correlation and by using the fingerprint data and the history data, a second access point; and
- triggering a handover from the first access point to the second access point.
- 34. The method of claim 33, further comprising:
- estimating, by the apparatus, a route of a user by correlating at least two most recent fingerprint data of the history data with the series of fingerprint data reflecting earlier movement of the user; and
- determining, by the apparatus, using the fingerprint data and the estimated route, the second access point.
- 35. The method of claim 33, further comprising:
- determining, by the apparatus, using the fingerprint data and the history data, the second access point being unavailable; and
- notifying, by the apparatus, a user of an apparatus before disconnection of the wireless communication service from the first access point.
- 36. A method comprising:
- determining, by an apparatus, fingerprint data relating to available access points;
- comparing, by the apparatus, the fingerprint data to known fingerprint data of a fingerprint database;
- updating, by the apparatus, the fingerprint database in response to the comparison revealing new fingerprint data; and
- storing, by the apparatus, history data of series of fingerprint data reflecting earlier movement of a user to a history database.
- 37. The method of claim 36, further comprising:
- determining, by the apparatus, the fingerprint data relating to available access points using sensors of an apparatus; and
- storing, by the apparatus, the fingerprint data to the history data of a series of fingerprint data.
- 38. The method of claim 36, further comprising:
- determining, by the apparatus, the fingerprint data relating to available access points using sensors of an apparatus;
- transmitting, by the apparatus, the fingerprint data to a crowdsourcing server;
- updating, by the apparatus, the fingerprint data to a crowdsourcing fingerprint database at the crowdsourcing
- receiving, by the apparatus, fingerprint data comprising at least part of the crowdsourcing fingerprint database.
- 39. The method of claim 36, wherein the fingerprint data comprises at least one of the following:
 - access point identifiers of available access points;
 - received signal strengths (RSS) associated with the available access point identifiers;

- received signal-to-noise ratios (SNR) associated with the available access point identifiers;
- location information; and
- timing information associated with the available access point identifiers.
- 40. An apparatus, comprising:
- a communication interface configured to receive wireless communication service from a first access point;
- a sensor configured to detect fingerprint data;
- a processor;
- a memory including computer program code;
- the memory and the computer program code configured to, with the processor, cause the apparatus to:
- detect a change in fingerprint data relating to available access points;
- correlate recent history data of a series of fingerprint data with history data comprised by a history database;
- determine, in response to the correlation and by using the fingerprint data and the history data, a second access point; and
- trigger a handover from the first access point to the second access point.
- **41**. The apparatus of claim **40**, wherein the memory and the computer program code are further configured to, with the processor, cause the apparatus to:
 - estimate a route of a user by correlating at least two most recent fingerprint data of the history data with the series of fingerprint data reflecting earlier movement of the user; and
 - determine, using the fingerprint data and the estimated route, the second access point.
- **42**. The apparatus of claim **40**, wherein the memory and the computer program code are further configured to, with the processor, cause the apparatus to:
 - determine, using the fingerprint data and the history data, the second access point being unavailable; and
 - notify a user of the apparatus before disconnection of the wireless communication service from the first access point.
- **43**. The apparatus of claim **40**, wherein any of the access points comprises at least one of the following:
 - a wireless local area network (WLAN) access point;
 - a Bluetooth access point;
 - an ultra-wideband access point; and
 - a cellular network base station.
- **44**. The apparatus of claim **40**, wherein the memory and the computer program code are further configured to, with the processor, cause the apparatus to:
 - maintain the fingerprint data in a fingerprint database; and maintain the history data in the history database.
- **45**. The apparatus of claim **44**, wherein the fingerprint database may be located in at least one of the following:
 - a user apparatus; and
 - a server apparatus.
- **46**. The apparatus of claim **44**, wherein the history database may be located in at least one of the following:
 - a user apparatus; and
 - a server apparatus.
 - 47. An apparatus, comprising:
 - a sensor configured to detect fingerprint data;
 - a processor;
 - a memory including computer program code;